

J2E-I

Model		J2E-10GP	J2E-15GP	J2E-25GP	J2E-40GP	J2E-60GP	J2E-75GP	J2E-100GP
Capacity (Nm ³ /min)		1.6	2.4	3.6	5.5	8.1	10.6	15
Connection (inch)		3/4" PT	1" PT	1" P	1-1/2" PT	1-1/2" PT	2" PT	2" PT
Power Supply (50/60 HZ)		220V / 1Ø				380V / 3Ø		
Ref. Comp. (KW) @ET10°C CT54°C		0.5	0.65	0.95	1.2	1.9	2.6	2.6
Operating Current (A) @ET5°C CT45°C		2.4	3	4.3	5	7.5	3.5	3.5
Full-Load Current (A) @ET10°C CT54°C		2.75	3.35	4.9	5.7	8.7	4	4
Refrigerant		R-134a			R-407C			
Fan motor (W)		50	50	50	95	125	250	250
Dimension (mm)	H	785	805	805	970	970	1060	1060
	L	580	680	680	780	780	1100	1100
	W	380	380	380	500	500	540	540
Net weight (kg)		40	50	54	83	93	127	173
Conditions (Air-Cooled)		J2E-10GP~J2E-100GP Air piping material : SUS #304 Inlet temperature : 5 ~ 80 °C (@60°C) Environment temperature : 2 ~ 42 °C (@38°C) Working pressure : 0.7 ~ 1.6 MPa (Excluded High-Pressure model)						

Customize products available upon request.