

# J2E-IV

Model		J2E-2000S	J2E-2500S	J2E-3000S	J2E-3500S	J2E-4000S	J2E-5000S
Max. capacity (Nm <sup>3</sup> /min)		230	280	330	380	430	530
Connection (inch)		10"FL	10"FL	10"FL	10"FL	12"FL	14"FL
Power source (60Hz)		3Phase 380V (220V、440V)					
Ref.comp. (Kw)		37.4	49.6	49.6	60.8	60.8	68.7
Operating current (A)		44.5	59.0	59.0	72.0	72.0	81.7
Full-load current (A)		62.9	83.4	83.4	101.7	101.7	115.5
Refrigerant		R407C (R22、R404A、R134a)					
Condenser (RT)		40	40	50	60	70	80
Dimension (mm)	H	2000	2000	2100	2100	2200	2200
	L	3400	3700	3700	3800	3400	3900
	W	1400	1400	1500	1500	1600	1600
Net weight (kg)		2300	2500	2800	3000	3300	4600
Operating scope		Inlet temperature : N type 5~50°C (@40°C) G type 5~80°C (@60°C)		Ambient temperature : 2~42°C (@38°C) Working pressure : ≤1.0MPa (@0.7MPa)		Cooling water flow : N type100×Max.capacity (L/hr) G type250×Max.capacity (L/hr)	
Remarks		Design condition @60Hz : 1. Ref. comp. ( Kw ) : @ET10°C, CT54°C 2. Operating current ( A ) : @ET5°C, CT38°C 3. Full-load current ( A ) : @ET10°C, CT54°C					

Customize products available upon request.