

J2E-III

SN Type Water Cooled

Model		J2E- 300S	J2E- 350S	J2E- 400S	J2E- 500S	J2E- 600S	J2E- 700S	J2E- 800S	J2E- 900S	J2E- 1000S	J2E- 1250S	J2E- 1500S
Capacity (Nm ³ /min)		43	50	61	72	79	93	116	125	134	155	180
Connection (inch)		4" FL	4" FL	4" FL	5" FL	5" FL	6" FL	6" FL	6" FL	8" FL	8" FL	8" FL
Power Supply (50/60 HZ)		380Volt 3Phase (220V 、 440V Optional)										
Ref. Comp. (KW) @ET10°C CT54°C 6.3		6.3	7.0	9.3	11.0	12.5	13.5	16.9	21.9	21.9	27.4	27.4
Operating Current (A) @ET5°C CT45°C		7.7	8.5	13.7	15.4	17.5	18.4	26.1	28.3	28.3	36.6	36.6
Full-Load Current (A) @ET10°C CT54°C		10.6	11.9	17.1	19.8	22.7	23.2	32.2	37.2	37.2	47.4	47.4
Refrigerant		R-407 c (R-134a 、 R-404a Optional)										
Condenser (RT)		7.5	7.5	10	12.5	12.5	15	20	20	20	25	30
Dimension (mm)	H	1670			1850			2050			2100	
	L	720			920			1000			1100	
	W	2300			2450			2500			2650	
Net weight(kg)		600	630	700	880	960	1050	1300	1480	1700	2100	2350
Cooling Water Vol. (Liter/Hr)		4300	5000	6100	7200	7900	9300	11600	12500	13400	15500	18000
Operating Scope		Inlet temp. : N Type 5~50°C (@40°C) / G Type 5~80°C (@60°C) Ambient temp. : 2~42°C (@38°C) Dew point : 2~10°C (@10°C) Working pressure : 7-10 Kg/cm2 (@7 Kg/cm2)										
Design Condition @60HZ		Ref. Comp. (kw) : @ET10°C 、 CT54°C Operating current (A) : @ET5°C 、 CT45°C Full-load current (A) : @ET10°C 、 CT54°C										

Customize products available upon request.